



## HHK 16S

Hydraulic Impact Hammer

JUNTTAN HHK 16S		
Max. energy	kNm (ft-lbs)	235 (173 700)
Drop height	mm (inch)	50 - 1500 (2 - 59.1)
Blows per minute		30 - 100
Ram weight	kg (lb)	16 000 (35 270)
Total weight including A-type drive cap	kg (lb)	27 000 (59 520)
Oil flow	l/min (gpm)	750 (200)
Operating pressure	bar (PSI)	230 (3 336)
Hoses - pressure line	mm (inch)	2 x 38 (1 ½)
- return line		2 x 38 (1 ½)
Drive cap types		A for metal tubes
Drive cap max. inner diameter	mm (inch)	A: O 1230 (48.4)
Larger drive cap diameters available on special request		
Suitable power packs		15 CCU - 30 CCU
Optional equipment		
<ul style="list-style-type: none"> <li>• guide claws</li> <li>• energy measurement device</li> </ul>	<ul style="list-style-type: none"> <li>• additional drive caps</li> <li>• pile sleeves</li> <li>• lifting cat</li> </ul>	<ul style="list-style-type: none"> <li>• power packs</li> <li>• additional noise insulation package</li> </ul>

Junttan Oy reserves the right to amend the specification without prior notice. Error and misprints reserved. March 3, 2005 - version M1HHK16S001.